

SECOND AVENUE HP ZONING OVERLAY DESIGN GUIDELINES

SECOND AVENUE HISTORIC PRESERVATION ZONING OVERLAY



METROPOLITAN HISTORIC ZONING COMMISSION

Metropolitan Government of
Nashville and Davidson County

Sunnyside in Sevier Park
3000 Granny White Pike
Nashville, Tennessee 37204
615-862-7970

www.nashville.gov
historicalcommission@nashville.gov

Adopted: August 1997
Revision Adopted: May 15, 2013
Italicized information revised 2021

INSIDE

<i>Introduction</i>	2
<i>Map of District</i>	9
<i>Rehab: Principles</i>	4
<i>Rehab: Design Guidelines</i>	6
<i>New Construction: Principles</i>	40
<i>New Construction: Design Guidelines</i>	41
<i>Signage: Intro</i>	50
<i>Signage: Design Guidelines</i>	52
<i>Demo: Principles</i>	66
<i>Demo: Guidelines</i>	67
<i>Appendix</i>	68



I. INTRODUCTION

WHAT IS REVIEWED:

IN A HISTORIC LANDMARK OVERLAY

- New construction (primary and secondary structures)
- Additions – increased footprint, height or building envelope of an existing structure
- Demolition (in whole or in part)
- Relocation of structures
- Construction of appurtenances (with the exception of portable storage buildings less than 100 square feet)
- Signage
- Repairs and Alterations to existing structures
- Setback Determinations

IN A HISTORIC PRESERVATION OVERLAY

- New construction (primary and secondary structures)
- Additions – increased footprint, height or building envelope of an existing structure
- Demolition (full or in part)
- Relocation of structures
- Construction of appurtenances (with the exception of portable storage buildings less than 100 square feet)
- Signage
- Repairs and Alterations to existing structures
- Setback Determinations

THE HISTORIC PRESERVATION ZONING OVERLAY

Please also see *MHZC Hand Book*.

Neighborhoods and districts in more than two thousand towns in the United States use historic zoning as a tool to protect their unique architectural characters. There are quantifiable reasons for historic zoning: it gives neighborhoods greater control over development; it can stabilize property values; it decreases the risk of investing in one’s house; it promotes heritage tourism; it protects viable urban housing stock; it preserves natural resources by conserving building materials. And there are less quantifiable, but equally important, reasons for conservation zoning -- it protects our past for future generations, it nurtures a sense of community, and it provides a sense of place.

Historic zoning overlays are **locally** designated and administered by the Metropolitan Historic Zoning Commission (MHZC), an agency of the Metropolitan Government of Nashville and Davidson County. Historic zoning overlays are applied in addition to the base or land-use zoning of an area. *Historic zoning overlays do not impact use.*

Like the National Register of Historic Places, neighborhood conservation zoning honors an area’s historical significance. With that recognition, certain exterior work on buildings—new construction, additions, demolition, and relocation—is reviewed to ensure that the neighborhood’s special character is preserved.

There are three types of historic zoning overlays: historic preservation, neighborhood conservation and historic landmarks. In addition to the projects reviewed in a neighborhood conservation zoning overlay, historic preservation and historic landmark overlays also review exterior alterations to existing buildings -- like replacing siding or installing a fence. Overlays with historic preservation or historic landmark zoning are not more historically significant than those with neighborhood conservation zoning; rather, the MHZC with neighborhood input and direction of the Council member determined that this overlay is most compatible with the goals of the neighborhood and the MHZC.



I. INTRODUCTION

WHAT ARE THE DESIGN GUIDELINES?

The Metropolitan Historic Zoning Commission (MHZC) is the architectural review board that reviews applications for work on properties within historic zoning overlay districts. Its nine members, appointed by the mayor, include representatives from zoning districts, the Metropolitan Planning Commission, the Metropolitan Historical Commission, architect(s) and others. Design review is administered according to a set of design guidelines. The guidelines are criteria and standards, developed jointly by the MHZC and property owners at the time of designation, which are used in determining the architectural compatibility of proposed projects. The guidelines provide direction for project applicants and ensure that the decisions of the MHZC are not arbitrary or based on anyone's personal taste.

The guidelines protect the district from new construction or additions not in character with the district and from the loss of architecturally or historically important buildings.

By state and local legislation, design guidelines for historic overlays must be in accordance with the *Secretary of the Interior's Standards for the Treatment of Historic Properties*—criteria developed by the National Park Service and used by private and public preservation organizations throughout the country. (Please see I.B.)

WHAT IS REVIEWED, continued:

IN A NEIGHBORHOOD CONSERVATION OVERLAY (also B&B Homestays)

- New construction (primary and secondary structures)
- Additions – increased footprint, height or building envelope of an existing structure
- Demolition (in whole or in part)
- Relocation of structures
- Setback Determinations

WHAT IS NOT REVIEWED IN CONSERVATION OVERLAYS

- Work that cannot be seen from the public right-of-way (not including alleys). To avoid a possible violation, the project should be evaluated by staff for assurance that a Preservation Permit is not necessary.
- Temporary Structures are ones that are erected for a period of 90 days or less and does not have permanent foundations.
- Portable buildings are those that are no larger than 10' x 10', do not have permanent foundations, designed and used primarily for the storage of household goods, personal items and other materials, are used on a limited basis and are not hooked up to utilities.
- Temporary banners/signage
- Temporary construction trailers
- Painting of wood

WHAT IS NOT REVIEWED IN HISTORIC PRESERVATION OVERLAYS

- Temporary banners/signage
- Temporary construction trailers
- Painting of wood



I. INTRODUCTION

PURPOSE OF THE DESIGN GUIDELINES

Within the zoning ordinance, “historic zoning” is used as the general term for Nashville’s three types of zoning overlay districts applicable to historic properties: historic preservation, neighborhood conservation, and historic landmark. The references to historic zoning in the ordinance and design guidelines are to be understood as neighborhood conservation zoning overlay, or simply conservation zoning.

A. Design guidelines are criteria and standards which the Metropolitan Historic Zoning Commission must consider in determining the appropriateness of proposed work within a neighborhood conservation zoning district. Appropriateness of work must be determined in order to accomplish the goals of historic and neighborhood conservation zoning, as outlined in Article IX (Historic Zoning Regulations), Metropolitan Comprehensive Zoning Ordinance:

1. To preserve and protect the historical and/or architectural value of buildings or other structures;
2. To regulate exterior design, arrangement, texture, and materials proposed to be used within the historic district to ensure compatibility;
3. To create an aesthetic appearance which complements the historic buildings or other structures;
4. To foster civic beauty;
5. To strengthen the local economy; and
6. To promote the use of historic districts for the education, pleasure, and welfare of the present and future citizens of Nashville and Davidson County.




I. INTRODUCTION

SECRETARY OF THE INTERIOR STANDARDS

- B. *By state law, all design guidelines for neighborhood conservation zoning overlays must comply with the Secretary of the Interior's Standards for Treatment of Historic Properties:*
 - 1. *A property will be used as it was historically or be given a new use that requires minimal change to its distinctive materials, features, spaces and spatial relationships.*
 - 2. *The historic character of a property will be retained and preserved. The removal of distinctive materials or alteration of features, spaces and spatial relationships that characterize a property will be avoided.*
 - 3. *Each property will be recognized as a physical record of its time, place and use. Changes that create a false sense of historical development, such as adding conjectural features or elements from other historic properties, will not be undertaken.*
 - 4. *Changes to a property that have acquired historic significance in their own right will be retained and preserved.*
 - 5. *Distinctive materials, features, finishes and construction techniques or examples of craftsmanship that characterize a property will be preserved.*
 - 6. *Deteriorated historic features will be repaired rather than replaced. Where the severity of deterioration requires replacement of a distinctive feature, the new feature will match the old in design, color, texture and, where possible, materials. Replacement of missing features will be substantiated by documentary and physical evidence.*
 - 7. *Chemical or physical treatments, if appropriate, will be undertaken using the gentlest means possible. Treatments that cause damage to historic materials will not be used.*
 - 8. *Archeological resources will be protected and preserved in place. If such resources must be disturbed, mitigation measures will be undertaken.*
 - 9. *New additions, exterior alterations or related new construction will not destroy historic materials, features and spatial relationships that characterize the property. The new work will be differentiated from the old and will be compatible with the historic materials, features, size, scale and proportion, and massing to protect the integrity of the property and its environment.*
 - 10. *New additions and adjacent or related new construction will be undertaken in such a manner that, if removed in the future, the essential form and integrity of the historic property and its environment would be unimpaired.*

The full set of Secretary of Interior Standards may be found online at www.cr.nps.gov/hps/tps/standguide/





I. INTRODUCTION

A SHORT HISTORY OF SECOND AVENUE

Listed in the National Register of Historic Places, the Second Avenue Historic District is Nashville's oldest downtown district. Second Avenue or Market Street, as it was known until 1903, was the commercial heart of the city in the latter half of the nineteenth century. This district is important for its outstanding examples of Victorian commercial architecture and for its representation of the development of this area as one of the most important industrial sections in Nashville's history.

Located along the east side of Second Avenue is one of the most outstanding collections of cast iron and masonry storefronts remaining in America. These buildings were constructed in the 1870s and 1880s in what was one of the earliest settled areas of Nashville. Built for shops and stores, most are three or four stories tall and are the full block deep, running back to First Avenue and overlooking the Cumberland River.

In 1804, in the area covered by this district there were two frame residences, a stone house which had been constructed as a fort, three frame store buildings, one frame tavern, and a one-story log house from which operated a ferry and keel boat landing.

The area continued to develop as a business district, with most of the owners living further out from this area. In 1809, several businesses had been established here, including a tannery, a silversmith shop, a bookstore, and a tavern.



Second Avenue around 1890, looking North from Broadway. Image from *Nashville Then and Now*.



Silver Dollar Saloon around 1890. It was named for the silver dollars embedded in every other floor tile. The inset shows patrons of the Silver Dollar posing for a snapshot. Image from *Nashville Then and Now*.



This photo from around 1872 was taken at the corner of First Avenue and Broadway and shows busy wharf activity.



I. INTRODUCTION

Nashville steadily grew as a center of trade and manufacturing, and its favorable location on the Cumberland River and the railroad which had been constructed up First Avenue caused the First and Second Avenues area to become a center for warehousing and distribution of these manufactured goods. During the decades following the Civil War, as the merchants and manufacturers prospered, the impressive buildings now existing on Second Avenue North, were constructed. Products of almost every description were distributed from this point.

As shipping on the Cumberland declined, buildings on Second Avenue fell into disuse or were used only as warehouses. During the 1970s, Nashville's interest in renovation and restoration led to the opening of restaurants, shops, and galleries in the century-old buildings: and Second Avenue is now the heart of a thriving entertainment area, with a mix of tenants and residents on upper floors.

In March of 1997, the Second Avenue National Register Historic District was designated a historic zoning district by the Metropolitan Council. As part of the designation process, the Second Avenue Design Guidelines were developed by the Metropolitan Historic Zoning Commission (MHZC) in conjunction with area property owners and others. Gaylord Entertainment provided valuable design and layout assistance.



Originally supplies were unloaded on First Avenue from Steamboats but by the 1920's railroad cars brought freight to the businesses along First Avenue. Rail spurs ran within a few feet of the buildings and truck drivers dispersed good in gasoline-powered vehicles. *Photograph by Marvin W. Wiles; courtesy of Nashville Area Chamber of Commerce.*




This view is from Church Street looking north on Second Avenue and shows how the automobile age of the 1920s started to change the look of Nashville.



I. INTRODUCTION



I. INTRODUCTION






II. REHABILITATION

Italicized sections of the guidelines contain interpretive information that is meant to make the guidelines easier to understand; they are not part of the guidelines themselves. Illustrations and photographs are intended only to provide example buildings and circumstances. It is important to remember that every building is different and what may be appropriate for one building or site may not be appropriate for another.

Façade Components



A General Principles: Street Level Facades

Original street-level facades, including storefronts, doors and entryways, display windows, transoms, bulkheads, and pilasters and columns, should be retained, and if needed, repaired using historically appropriate materials and methods.

Replacements of street-level facades should be in keeping with the style and period of the building.

The use of contemporary materials for the replacement elements of street-level facades may be appropriate if they possess characteristics similar in scale, design finish, texture, durability, and detailing to historic materials and meet *The Secretary's Standards*.

Replacement materials are appropriate if:

- The original materials no longer exist
- The original material is unknown; or
- The new material possess characteristics similar in scale, design finish, texture, durability and detailing to the historic material.



II. REHABILITATION

A. Guidelines: Storefronts

1. Historic storefronts, their component elements, and other aspects of appearance including the original entrance configuration, plane, and recess should be retained.
2. Deteriorated or damaged storefronts or component elements should be repaired using historically appropriate materials.
3. If replacement storefronts or component elements are necessary, replacements should be compatible with the materials, composition, design, texture, and general appearance of the original. Replacements should use physical or photographic evidence to replicate the original appearance. If evidence is not available, the replacement storefront should use arrangement, features, materials, and proportions typically found on buildings of the same style and period of the building involved.
4. Original entrances configuration, plane, recess and other visual qualities should be retained.



Historic storefronts should be retained and, if needed, repaired using materials that match the historic materials.



This modern storefront appropriately replicates the missing historic storefront through its incorporation of the typical storefront elements of wood-paneled bulkheads, and clear glass display windows with wood frames.




II. REHABILITATION

B. Guidelines: Doors and Entryways

1. Original doors, entryways, and related elements should be retained.
2. Deteriorated or damaged doors or entryways should be repaired using historically appropriate materials.
3. If replacement doors are necessary, replacements should replicate the originals. If original doors do not remain, replacement doors should be of wood and the proportion of glass to door should be comparable to the proportion of display windows to bulkheads.
4. Ornamental, frosted, or stained glass in front doors are generally not appropriate, except where incorporated into window graphics and/or business identity.
5. If doors or entrances do not conform to building or accessibility codes, the originals should be retrofitted to conform. If this is not feasible, replacement doors should be compatible with the original storefront. Variances to building codes may also be sought when the building meets the intent of the code requirements.
6. Glass used in replacement doors should be clear.
7. Generally, new entryways should not be introduced to public facades, unless needed for access to an upper floor or a secondary building use. If a new entrance is needed, it should be compatible with the style and period of the building.



These and other historic doors should be retained. If repairs are needed, materials such as wood or wood epoxy should be used so that they continue to have their historic appearance.



Appropriate replacement storefront door designs.



New doors that change the original opening dimensions and design, as seen above on First Avenue, are not appropriate.




II. REHABILITATION

C. Guidelines: Display Windows

1. Original display windows and their component elements should be retained.
2. Deteriorated or damaged display windows should be repaired using historically appropriate materials.
3. If replacement display windows are necessary, replacements should replicate the originals. If original display windows do not exist, replacements should be appropriate for the building's style and period.
4. Appropriate replacement elements include individual or grouped single-light clear-glass panes and simple wood, copper, bronze anodized aluminum, or baked-enamel aluminum frames.
5. Glazing should be clear glass. Ornamental, frosted, spandrel, or stained glass display windows are not appropriate.
6. Display windows should remain visible and not be concealed or enclosed.
7. If privacy or shade other than that afforded by awnings is needed, interior shades or blinds are appropriate.



Original display windows should be retained and, if needed, repaired using materials that preserve their historic appearance.



New storefronts should have appropriately sized and configured display windows.



II. REHABILITATION



D. Guidelines: Transoms

1. Original transoms and their component elements should be retained.
2. Deteriorated or damaged transoms should be repaired using historically appropriate materials.
3. If replacement transoms are necessary, replacements should replicate the original. If original transoms do not exist, replacements should be appropriate for the building's style and period.
4. Appropriate replacement elements include single or multi-light clear-glass panes and simple wooded or metal frames.
5. Historic transoms should remain visible and not be covered or enclosed.

Historic transoms should be retained and preserved.





II. REHABILITATION

E. Guidelines: Bulkheads

1. Original bulkheads and their component elements should be retained.
2. Deteriorated or damaged bulkheads should be repaired using historically appropriate materials.
3. If replacement bulkheads are necessary, replacements should replicate originals. If original bulkheads do not exist, replacements should be appropriate for the building's style and period of construction.
4. Appropriate replacement elements include paneled and painted wood, brick, and metal.
5. Historic bulkhead materials should remain visible, not concealed beneath added materials.



Historic bulkheads should be repaired rather than replaced.




Appropriate designs for frame bulkheads if original bulkheads are missing.



The painted, paneled wood is an appropriate modern bulkhead design.



II. REHABILITATION



These columns and capitols are historic and an important stylistic element. They and other historic columns and pilasters should be retained.



F. Guidelines: Cast Iron, Wood Pilasters, and Columns

1. Original pilasters and columns should be retained.
2. Original cast iron columns and pilaster shall not be concealed or obscured.
3. Applying paint or another surface treatment is an appropriate preservation measure.
3. Deteriorated or damaged columns and pilasters should be repaired using historically appropriate materials.
4. If replacement pilasters or columns are necessary, replacements should match or complement originals in configuration and design.
5. Appropriate replacement materials include wood, cast iron, sheet metal, and stone.
6. Owners are encouraged to replace pilasters and columns that were original to the building but have been removed.



II. REHABILITATION

G. Guidelines: Cornices

1. Original cornices and other detailing should be retained.
2. Deteriorated or damaged cornices or other detailing should be repaired using historically appropriate materials.
3. If replacement cornices are necessary, replacements should replicate the originals. If original cornices do not exist, replacements should be appropriate for the building's style and period. New cornices shall not be added where none existed originally.
4. Appropriate replacement materials include sheet metal and wood.
5. Owners are encouraged to replace cornices that were original to the building but have been removed.



Some storefronts have their own cornices. These should also be retained and remain visible.



The section of the cornice on the right has deteriorated but originally matched the intact cornice on the left. The missing cornice should be rebuilt to match the existing cornice on the building.



II. REHABILITATION

Upper Façades

General Principles

Original appearance and details of upper-story facades should be retained.

If repairs are needed, it should use historically appropriate materials and methods.

Replacements to facades should be in keeping with the style and period of the building.

The use of contemporary materials for the replacement elements of facades may be appropriate if they possess characteristics similar in scale, design finish, texture, durability, and detailing to historic materials and meet *The Secretary's Standards*.

Interior changes that affect the exterior appearance of upper facades including lowering ceiling heights or raising floor levels should be avoided.





II. REHABILITATION

H. Guidelines: Windows

1. Original windows and window openings, including dimensions, sash, (configuration, number and arrangement of panes), materials, and detailing (sills, lintels, and decorative hoods) should be retained.
2. Deteriorated or damaged window openings, windows, and window surrounds should be repaired using historically appropriate materials.
3. If replacement windows or window surrounds are necessary, replacements should replicate originals. If original windows do not exist, replacements should be appropriate for the building's style and period.
4. If the original windows are missing, replacement windows should use wood, anodized aluminum, or baked-on-enamel aluminum frames and should have single-light or multiple-light clear-glass panes to match the style and period of the building. Mult-pane windows should be true or simulated divided lights with a spacer bar between the glass. Snap-on or between the glass muntins are inappropriate.
5. Steel windows should be replaced with steel or aluminum designs that replicate the appearance of the original window.
6. Window grills, balcony rails, and shutters are not appropriate window treatments.



Original wood windows should be preserved..





II. REHABILITATION



A one-over-one window design can be appropriate when the original grill pattern is unknown.

7. Window openings, surrounds, or other elements not original to a building should generally not be introduced to the public facades of the building.
8. Should storm windows be desired, their dimensions should match window dimensions in order to conceal their presence. Frames should be set within the window opening and attach to the exterior sash stop; if aluminum, they should have an anodized or baked-on enamel finish.
9. Self installed snap, clip or glue type muntins on windows are not permitted. Muntins set within the vacuum between glass panes on windows are not approved.



II. REHABILITATION

I. Guidelines: Walls

1. Original walls, including size and location of openings, recesses, detailing, and ornamentation should be retained. The plane of the exterior wall shall be retained.
2. Balconies should not be added to public facades.
3. Decorative elements such as cornices, brick corbelling, arches, brackets, terra cotta detailing and any other original wall detail shall not be altered.
4. New decorative elements should not be added where none existed.




Original façade walls should be retained without the addition of balconies or other non-historic building elements.



II. REHABILITATION

J. Guidelines: Brick, Stone, and Other Masonry



Preserve and maintain historic masonry.



The brick above was cleaned using a harsh method that has removed the hard protective outer surface of the brick.

1. Original brick and brick pattern should be retained..
2. The use of detergent cleaners and chemical stain and paint removers to clean masonry or remove paint is appropriate under most conditions. Abrasive or high-pressure cleaning methods are destructive and should not be used.
3. Silicone-based water sealants are not recommended for use on historic masonry.
4. Historic masonry should remain visible and not be concealed or obscured.
5. Where brick is deteriorated, replacement may be appropriate. When replacement is approved, new brick shall be of the same color, textures, and size; new brick shall be laid in the same pattern as the original, with similar joints, tooling and mortar as the original.
6. Repointing with a hard (Portland cement) mortar is destructive to historic brick and masonry. Flexible mortar, made from mixing hydrated lime cement and natural sand, should be used when repointing is necessary.
7. Mortar used in repointing should match the historic mortar in width, depth, color, raking profile, composition, and texture.
8. Brick shall not be sandblasted or cleaned in an



II. REHABILITATION

abrasive manner. Sandblasting accelerated deterioration of the brick and allows moisture to penetrate the brick.

9. Painting of brick may be appropriate if: brick has previously been painted; or brick is too deteriorated to withstand weather. A red brick stain, approximating the original color of the building's brick should be used.
10. Painting of stone, terra cotta, or glazed brick is not appropriate.



Historic masonry should not be concealed or obscured.



Above is an example of an improper repair that uses bricks of a different color and dimension from the original and the mortar joints also do not match the original tooling.



II. REHABILITATION

K. Guidelines: Decorative Elements

1. Original decorative elements such as cornices, brick corbelling, arches, brackets, and detailing should be retained without alteration.
2. Deteriorated, damaged, or missing decorative elements should be repaired using historically appropriate materials. Replacement of decorative elements that are missing or unable to be repaired and located on upper facades may use modern materials if the material matches the original in design, texture and workability.
3. Owners should not add decorative elements to a building, unless there is physical or pictorial evidence.
4. Decorative or ornamental detailing should not be added to buildings unless there is physical or photographic evidence that shows the detailing was original to the building. New designs should be appropriate to the style and period of the building.



Decorative brick corbelling frames this window.



II. REHABILITATION

L. Guidelines: Roofs and Chimneys

1. Original roof configuration, including coping, parapets, and materials should be retained.
2. Appurtenances related to outdoor use of roofs, including elevator shafts, railings, canopies, and any other elements visible from the street, should be compatible with the building should not obscure character-defining features. Guidelines for brick and mortar should be followed for chimney maintenance.
3. Appropriate roof coverings include standing seam metal, composite asphalt, rolled roofing, and rubber membrane roofing. Most rooflines in the Second Avenue district are flat or sloped. These roof forms should not be altered unless based on historical documentation.
4. Roof mounted mechanical units should be located so as to be inconspicuous from street level.
5. Roof additions if approved, should be located so that they are inconspicuous from the public right-of-way and do not damage or obscure character-defining features.



The gabled pitch of this roof is found on some buildings in the district. Its historic pitch and appearance should be retained.



Mechanical units should be sited on rear facades.



II. REHABILITATION

PAINT

General Principle

The painting of wood and metal surfaces is not reviewed by the MHZC. The painting and staining of masonry (brick and stone) are reviewed by the MHZC. Unless needed to cover mismatched or damaged masonry, or as a preservation measure for pitted brick, masonry not previously painted or stained should remain unpainted and unstained.



The historic painted signage, like this one on First Avenue, should be retained wherever possible.



II. REHABILITATION

M. Guidelines: Paint

1. Building owners are encouraged to remove paint from masonry. Gentle, non-abrasive chemical cleaning is an appropriate way to remove paint.
2. Painting of stone and brick is generally not appropriate.
3. Staining of masonry may be appropriate if: brick has previously been painted; or if brick has been sandblasted or otherwise damaged and is too deteriorated to withstand weather. A brick color approximating the original color of the building's brick should be used.
4. Historic painted signage on exterior brick walls should be maintained.
5. Brick sealers are not recommended for exterior brick as it may cause damage to the brick face over time.



II. REHABILITATION

REAR ELEVATIONS

General Principle

Rear elevations are service-oriented, and are an appropriate place for infrastructure elements such as gutters and downspouts, mechanical systems, and fire stairs. Despite their less public nature, original materials and features should be preserved and maintained.



Most Second Avenue buildings on the east side of the street extend from Second Avenue to First Avenue; therefore, First Avenue is considered a “rear elevation.”



II. REHABILITATION

N. Guidelines: Rear Elevations

1. Generally, original materials and features on rear elevations should be preserved and maintained.
2. The appearance of rear elevations can be enhanced through the screening of infrastructure elements and the use of signage and awnings.
3. Rear elevations are appropriate locations for mechanical systems, meters and fire stairs.



Rear elevations are traditional locations for mechanical units, gutters and downspouts and secondary entrances. This is also true for First Avenue, which is the “rear” of buildings facing Second Avenue; however, installing “storefronts” into what was originally vehicular access is also appropriate, as seen below.





II. REHABILITATION

O. Guidelines: Gutters and Downspouts

1. Generally, gutters and downspouts should not be located on the public façades of buildings. Such elements should be installed on the rear elevations of buildings.
2. The installation of gutters and downspouts should not result in the removal or obstruction of historic building elements.



Downspouts on front or side facades should be painted to blend with the paint or masonry color.



Downspouts should channel water away from the building foundation.



II. REHABILITATION

P. Guidelines: Mechanical Systems

1. Equipment such as condensers, air conditioners, meters, and conduits should not be visible from the street. Rear elevations and roof locations that are not visible from the public rights-of-way are appropriate locations for this equipment.
2. The installation of mechanical systems should not result in the removal or obstruction of historic building elements.
3. Landscape elements such as fencing or low masonry walls should be used to shield ground-level equipment from view and still allow service access.



Mechanical units and appurtenances such as satellite dishes should be sited at rear facades.



II. REHABILITATION

Q. Guidelines: Fire Escapes



1. Fire escapes should be located on rear elevations, with the exception of First Avenue. Their installation on public facades is not recommended.
2. Fire escapes may be either open or enclosed as required by fire codes.
3. If enclosed, their surfaces should be of wood siding, brick veneer, or stucco.
4. If open, they should be of metal or wood.

Fire escapes should be sited at rear facades.



II. REHABILITATION

AWNING & CANOPIES


General Principle

Awnings may be appropriate when located within existing window and storefront openings and are consistent with the overall character of the building in terms of type, size, placement, color and material.

Canopies, including marquees, may be appropriate if such design is architecturally compatible with the overall storefront design in terms of size, location, color, and material, and does not detract from the character of the building.



II. REHABILITATION



The placement of these awnings above the storefront transom, above an existing secondary entrance, and above existing upper façade windows is appropriate.

R. Guidelines: Awnings

1. Awnings placement should not obscure or damage architectural details or character defining features. Appropriate storefront placement is across the storefront above the transom.
2. Awnings may be fixed or retractable and should be placed within major architectural framing members, such as arches, columns or post and lintel systems.
3. Storefront awnings should project no more than seven feet from the building and should cover no more than one-third of a storefront window display height.
4. The most appropriate design for awnings is a shed form. The use of shed awnings for upper façade windows is also appropriate. Curved forms are not appropriate, unless there is historical evidence for their use on a building or if the shape of the opening dictates such.
5. Awnings shall not be backlit. Spotlighting of awnings from above is appropriate.
6. Awning material shall be opaque, not translucent, in canvas, cotton duck, or similar natural materials. Plastic or vinyl awnings should not be used.



The placement, above the storefront and transom, and shed form of this awning are appropriate. Likewise, its opaque construction material is appropriate. As illustrated, awnings may include graphics or signage.



II. REHABILITATION

S. Guidelines: Canopies

1. Canopies should not obscure windows or architectural details.
2. Canopies should be constructed of materials compatible with the storefront of the building, such as metal and wood.
3. Lighting and signage on canopies shall be consistent with guidelines for signage and awnings.

II. REHABILITATION

LIGHTING

General Principle

Light fixtures should be as simple and unobtrusive as possible.



II. REHABILITATION

T. Guidelines: Lighting

1. If lighting is installed, it should be concealed or simple and unobtrusive in design, materials, and relationship to other façade or elevation elements.

- *Colored bulbs or filters are not appropriate. Warm white light that does not distort the color of the building's materials or finishes is appropriate.*
- *Floodlights, spotlights, mercury vapor, sodium vapor, fluorescent tube lamp and CFL lamps and/or colored lights are not appropriate.*
- *Lighting fixtures and illumination should not flash, spin or be animated in any manner.*
- *Conduits, junction boxes and wires should not be visible on street-facing facades.*
- *Rope lighting (also known as "strand lighting, lite ropes, flexible impact lighting, tubular lighting, and string lighting) is prohibited unless concealed behind a cornice.*

2. Light should be directed toward the façade instead of outward. Building facades may be illuminated through uplights mounted above the storefront cornice.

- *Light fixtures installed directly above or behind the storefront cornice are appropriate; however, light fixtures above those locations are inappropriate.*
- *Exterior lighting of rooftop additions is inappropriate as the visibility of rooftop additions should be minimized. Rooftop decks may be lighted with ground and/or table lighting. Entrances of rooftop decks may have minimal lighting to provide for safety.*
- *Hardware should be installed in masonry joints rather than through the brick.*
- *A Gobo light may be appropriate if the projection is directed to the sidewalk only and not to a building façade;*



The simple design, inward direction of the light, and dark metal construction of this light fixture make it appropriate.



The simple, industrial design and inward direction of the light make this light fixture appropriate.



II. REHABILITATION

the fixture is small, unobtrusive and obscured from view; the fixture does not require removal of a character-defining feature, and there is only one per building.

3. Dark metals are appropriate materials for light fixtures.
 - *The fixture could also be of a color to match the surface upon which it is mounted.*

4. Concealed, indirect, or spot lighting is appropriate for exterior signage. Visible fluorescent bulbs are not appropriate.



II. REHABILITATION



III. NEW CONSTRUCTION

NEW CONSTRUCTION

General Principles

These guidelines shall apply only to the exteriors of buildings and to areas of lots visible from public rights-of-way.

The public facades – street related elevations – of proposals for new buildings shall be more carefully reviewed than other facades.

New construction should be consistent with existing buildings along a street in terms of height, scale, setback, and rhythm; relationship of materials, texture, details, and color; roof shape; orientation; and proportion and rhythm of openings.


Because new buildings usually relate to an established pattern and rhythm of existing buildings, the dominance of that pattern and rhythm must be respected and not disrupted.

In the case of planned new construction between buildings of equal height or varying heights, an individual judgment will be made by the MHZC as to the compatibility of the design.

Reconstruction may be appropriate when it reproduces facades of a building which no longer exists and which was located within the boundaries of the historic district if: the building would have contributed to the historical and architectural integrity of the area; if it will be compatible in terms of style, height, scale, massing and materials with the buildings immediately surround the lot on which the reproduction will be built; and if it is accurately based on pictorial documentation.



This building was reconstructed based on photographs.




The Preservation Press



III. NEW CONSTRUCTION

A. Guidelines: Height

1. New buildings must be constructed to a height which is compatible with the height of adjacent buildings or buildings within the historic district.
2. Infill buildings which directly front on Second Avenue shall not exceed a height greater than 65 feet or 5 stories. Infill buildings which directly front on Second Avenue may rise an additional 15 feet (80 feet total or 6 stories), at a distance of 30 feet from the main façade of the building and 20 feet from First Avenue for those buildings on the east side of the street.
3. Infill buildings which are constructed on corner lots facing Second Avenue may rise an additional 15 feet (80 feet total or 6 stories), at a distance of 30 feet from the main façade of the building and 20 feet from the secondary street.
4. Infill buildings shall be a minimum of 30 feet or 2 stories in height.



Appropriate height for infill construction and rooftop additions for buildings on the west side of Second Avenue. The 6th story of new buildings on the east side of the street sit back 30' on the Second Avenue side and 20' on the Frist Avenue side.



This new building on Second Avenue is appropriate for the district in terms of roof shape and height.


III. NEW CONSTRUCTION

B: Guidelines: Scale

1. The size of a new building, its mass in relation to open spaces, and its windows, doors, openings, and appurtenances should be visually compatible with the surrounding buildings.
2. In the event that multiple lots or parcels are assembled within the historic district, buildings shall be designed to be compatible with the adjacent structures. Existing traditional and historic buildings are 20 to 50 feet wide. New structures should employ design techniques to break the facades along the right-of-way into multiple vertical elevations as previously described.
3. All new buildings should have a base, middle, and cap. Traditionally, buildings were composed of these three basic elements. Adhering to this form will help reinforce the visual continuity of the area.
4. The first floor height shall be a minimum of 16 feet from finished floor to finished floor. Upper floor heights should appear to be similar to historic structures in the district.



Appropriate scale for new construction.






III. NEW CONSTRUCTION

C: Guidelines: Setback and Rhythm of Spacing


1. The setback from the street and side property lines established by adjacent or contiguous buildings shall be maintained. When a definite rhythm along a street is established by uniform lot, building width, or bay patterns within a building façade, infill buildings should maintain the rhythm.
2. New buildings should be constructed in line with adjacent historic structures. Corner buildings should avoid setbacks or open corner plazas that disrupt the continuity of the street wall.
3. New buildings shall front 100% of the primary street and, where applicable, a minimum of 85% of the secondary street.



The infill building on this block of Broadway appropriately maintained the established setback and rhythm of spacing.



Appropriate model for the alignment of new construction.



New construction should maintain the continuity of street walls.



III. NEW CONSTRUCTION



D: Guidelines: Roof Shape

1. The roofs of new buildings shall be visually compatible with the roof shape and orientation of surrounding buildings.
2. The roof forms of buildings within the district are typically flat or have a gentle slope behind a parapet wall.

The roof shapes for new construction should mimic the roof shapes of existing buildings. On this block, as is typical for the district, appropriate roof shapes are flat or very slightly sloped and some have gabled parapet walls.




III. NEW CONSTRUCTION

E: Guidelines: Proportion and Rhythm of Openings

1. The relationship of width to height of windows and doors and the rhythm of solids to voids in new buildings shall be visually compatible with the surrounding buildings.
2. The design of the street level of new buildings is crucial in establishing the commercial vitality. At least 80% of the street level façade of a new building shall be transparent (i.e., doors and windows) to provide visual interest and access for the pedestrian. This guideline is most important on Second Avenue where most of the buildings have commercial ground floor storefronts. First Avenue and side facades may have less glazing.
3. Define a clear primary entry. Doorways on primary facades shall appear similar to those used historically. The primary entrance should be defined with a canopy or other architectural feature.
4. Upper floor windows should be at least twice as tall as they are wide.

Windows on upper floors should not be taller than windows on the main floor since historically first floors have higher ceilings than upper floors and so windows were typically taller on the first floor.

5. Door and window openings should be recessed on masonry buildings, as they are traditionally, rather than flush with the rest of the wall.
6. On corner buildings, glazing shall turn the corner facing the secondary street a minimum of one structural bay or 16 feet, whichever is the greater.



Appropriate vertical rhythm and window alignment is shown on this new building to the left. The building on the right has an appropriate amount of transparency.



Appropriate proportions for upper-floor windows.

III. NEW CONSTRUCTION

F: Guidelines: Relationship of Materials, Texture, Details, and Material Color



The recent building constructed on Broadway, around the corner from Second Avenue, used materials similar to those of its neighbors in its brick construction, clear glass window panes, and wooden doors.


1. The relationship and use of materials, texture, details and material colors of a new building's public facades shall be visually compatible with or similar to those of adjacent buildings, or shall not contrast conspicuously.
2. Masonry materials were primarily used in the historic district, and should continue to be predominant. Contemporary materials may be used if they possess characteristics similar in scale, design, finish, texture, durability, and detailing to historic materials and meet *The Secretary's Standards*. Exterior Insulation Finish Systems (EIFS) and vinyl are not appropriate exterior materials.
3. Wood, brick, stone, and metal were used for window, door and storefront surrounds and should be used for new buildings.
4. Storefront façade materials may vary in keeping with the materials of the existing buildings. Stone, glazed tile, painted wood, and brick are all appropriate materials.
5. Tinted glass, reflective glass, or colored glass may not be used for windows.
6. Large expanses of featureless materials are not appropriate.
7. The color of new building materials should be compatible with historic buildings within the district.




III. NEW CONSTRUCTION

G: Guidelines: Orientation

1. The site orientation of new buildings shall be consistent with that of adjacent buildings and shall be visually compatible. Directional expression shall be compatible with surrounding buildings, whether that expression is vertical, horizontal, or non-directional.
2. Primary building entrances shall be oriented to the primary street.



III. NEW CONSTRUCTION



Required setbacks for rooftop additions.

H: Guidelines: Additions to Existing Buildings

1. New additions to existing buildings should be kept to a minimum and should be compatible in scale, materials, and texture; additions should not be visually jarring or contrasting.
2. Additions should not be made to the public facades of existing buildings.
3. Additions should not contribute to the loss of, or obscure, historic character-defining features or materials.
4. Additions to historic buildings should be minimal. Additions normally not recommended on historic structures may be appropriate for non-historic buildings, if the addition will result in a building that is more compatible with the district.
5. Rooftop additions should not exceed one story in height (or 15') and should be set back a minimum of 30 feet from the Second Avenue façade of the building, 10 feet from First Avenue, and 20' from a secondary street if it is a corner building

Rooftop railings should set back from each street facing wall by 8'.

Railings should not be used to support additional elements such as speakers, lighting, plants or signage.


In locations where railings are visible from the street, the materials should minimize the impact of the railing. Materials such as butt-joint glass or horizontal steel cable, may be appropriate.



III. NEW CONSTRUCTION

I: Guidelines: Parking/Parking Structures, Plaza, Arcades, Landscape and Open Space

1. Parking, parking structures, plazas, arcades, landscape and open space may be appropriate components of new construction when the design of such development contributes to the overall character of the district and the streetscape, and the new construction is consistent with the design guidelines for new construction.
2. Parking structures should be wrapped with retail space or other active use along the street edge.
3. Curb cuts are not permitted on Second Avenue, and vehicular access should occur at the alley on properties that abut alleys or on First Avenue.
4. All applicable guidelines for new construction shall be followed for parking structures.
5. Removal or demolition of existing historic buildings, or portions of buildings, to create a plaza, arcade, or open space is not appropriate.



Parking added to the historic district should have commercial retail space on the first floor.



IV. SIGNAGE

INTRODUCTORY PROVISIONS

Intent

The purpose of these regulations is to preserve the historic character of the overall district and individual historic buildings follow the basic principles and guidance of the “Downtown Codes Sign Standards” as adopted 1/30/2013. The “Downtown Codes Sign Standards” breaks signage guidance up by “street types.” The Second Avenue Historic Preservation Zoning Overlay closely follows the guidance for “Pedestrian Street” type.

Applicability

- These sign regulations apply to all properties within the Second Avenue Historic Preservation Zoning Overlay.
- Signage that is cut into the face of the building is prohibited.
- Signage located on the interior of a building or attached to the inside of glass windows is not reviewed.
- Sandwich board signs and 3-dimensional sidewalk signs that are brought into the building at the close of each business day shall not be reviewed by the MHZC but may require review by Public Works.
- Historic signage should be retained. Removal of historic signage may take place as a Modification.

Sign Permit Applications

Applications for sign permits shall be made with and reviewed by the Metro Historic Zoning Commission (MHZC). All sign applications that do not involve Modifications shall only require MHZC administrative approval.

Common Sign Plan

A common signage plan regulates signage for multiple businesses or tenants within one building or complex. A

common sign plan is mandatory for all new developments and sign Modifications.

- A common signage plan shall provide for consistency among signs with regard to at least four of the following: materials; location of each sign on the building; sign proportions; color scheme; lighting; lettering or graphic style.
- The common signage plan shall establish an allowable area of signage for existing and future tenants with regard to all allowed sign types.
- The common signage plan shall indicate existing nonconforming signs as well as the amount and locations of on-premise signage to be allocated to each tenant under the new plan.

MODIFICATIONS

Sign Permit Modifications

Requests for modifications to sign standards are reviewed by the Metro Historic Zoning Commission. If the property is also within a MDHA redevelopment district, approval from the MHZC is all that is needed. Two additional types of Modifications for signage related permits may be requested and are outlined below.

Modifications for Exceptional Design

Creative signage that does not fit the specific regulations of these guidelines may be considered by the MHZC, based on its merits, as they relate to all of the following design criteria:

- Architecture
- The configuration or location of the building or property
- Building scale
- Legibility
- Technical competence and quality in design, construction and durability

Applications for this type of Modification require submittal of a common sign plan for the property in question. Approval of any related structure (i.e. canopy) will require review by all applicable agencies. Exceptional design modifications shall



IV. SIGNAGE

not permit electronic changeable copy where it is otherwise not permitted.

Modifications for Tourist-Oriented Businesses

Tourist-oriented businesses within DTC zoning may receive Modifications to allow greater sign area and use of digital technology. To qualify as a tourist –oriented business a business shall:

- Have a minimum permanent fixed seating capacity of 500; and
- Offer lawful activities or services to the general public of cultural, historical, recreational, educational, or entertainment purposes.

Applications for this type of Modification require submittal of a common sign plan for the property in question. Approval of any related structures (i.e. canopy) will require review by all applicable agencies. Tourist-oriented business Modifications shall be reviewed according to the design criteria listed under Modifications for Exceptional Design, in addition to the following:

- Large electronic or illuminated signs shall not adversely impact residential or hotel uses.
- All signs shall conform to the lighting standards of the DTC.
- See section on changeable copy for additional information regarding changeable copy.

RIGHT OF WAY ENCROACHMENTS

Where a sign is proposed to encroach into the public right-of-way an application shall be made with the Public Works Department in addition to the sign permit application with the MHZC. Both applications shall include the requirements of the Public Works Department available at their website: www.nashville.gov/Public-Works/Developer-Services.aspx, in addition to the MHZC submittal requirements.

NON-CONFORMING SIGNS

Sections 17.40.660 and 17.40.690 of the Metro Zoning code apply. This section further clarifies them.

Building Signs

A sign shall be brought into compliance with the provisions of these design guidelines if a sign permit is required to rebuild the sign. This does not include a panel change in a non-conforming cabinet sign, which shall be permitted.

Ground Signs

An existing ground sign may change the face or panel of a sign that does not meet the area or height standards within these design guidelines. However, in no instance shall there be an increase in the degree of nonconformity. All new panels shall conform to all illumination standards therein.

A sign shall be brought into compliance with the provisions of these design guidelines if at any time the sign is altered, repaired, restored or rebuilt to the extent that the cost exceeds fifty percent of the estimated replacement cost of the sign (in current dollar value). All permits within any six consecutive calendar months shall be aggregated for purposes of measuring the fifty percent standard.

All Signs

If the alteration or repair is caused by involuntary damage or casualty, the design may be altered or repaired to its pre-damaged condition.

Repair and Maintenance

A sign may be removed or taken off-site for repair and maintenance. The sign must be returned to the original location within 90 days of removal.



IV. SIGNAGE

A. Allocation of Sign Area

The maximum sign area for each type of sign is established in the following tables. Specific requirements for each sign type are shown on the subsequent pages.

For each cell in the table, there is a maximum allowed sign area that may be utilized with any combination and any number of signs associated with that cell, unless otherwise noted.

The measurements for “linear feet” shall be at grade.

Building Signs

Wall Sign	1.5 square foot of sign area per 1 linear foot of building façade or 36 square feet, whichever is greater.
Awning Sign	When a projecting sign is used on the building, an additional 0.50 square feet of sign area per 1 linear foot of building façade shall be permitted, for a total 2 square feet per 1 linear feet of building façade.
Canopy Sign	
Projecting Sign	
Shingle Sign	9 square feet per sign

Ground Signs

Monument Sign	24 square feet
---------------	----------------

Skyline Signs—area determined by average height to of building

75’ to 100’	480 square feet
101’ to 200’	600 square feet
201’ and taller	720 square feet



IV. SIGNAGE

This page intentionally left blank.

IV. SIGNAGE


B. GENERAL STANDARDS

Materials

All permanent, on-premises signs shall be constructed of a rigid, weatherable material such as hard plastic, wood, MDO plywood, aluminum, steel, PVC, glass, fiberglass and or Plexiglass. On-premises permanent signs shall not be constructed of nonrigid materials including, but not limited to, vinyl, fabric, canvas, or corrugated plastic. The provisions of this subsection shall not apply to approved, permitted canopies, awnings and porticoes.

Building Façade and Street Frontage Measurement

In determination of number of stories of a building, rooftop additions shall not be considered within the number of



stories.

OTHER SIGN TYPES

Non Street Facing Signs

Non street-facing building façades and alley frontages, not otherwise regulated, are allocated 1 square foot of sign area per 1 linear foot of building façade, to a maximum of the sign area permitted for the primary street frontage.

This includes lots adjoining open spaces, pedestrian walkways,

or parking areas. Ground signs are not permitted on non-street facing building façades or alley frontages.

Temporary Signs

Temporary signs shall follow the standards of 17.32.060.

Painted Signs

All painting of masonry, whether for signage, to change the color of the building, or for artwork shall be reviewed by the MHZC. (Please see section on “walls” for guidance on painting a masonry building.) Painted signage may be considered by the MHZC as modification, based on the following design criteria:

- Should only be added to rear elevations or exposed upper secondary elevations and should not cover transoms, columns, cornices, decorative elements, openings and architectural features or require the enclosure of openings.
- Painted on main façades or the first level of buildings are not appropriate.
- Generally, a painted sign should not be more than 125 square feet in size.
- Painted signs should serve as a sign for the current occupant(s) and should not advertise off-site businesses or products.
- Generally, painted signage should not have lighting; however, if lighting is necessary, it should be between one and two gooseneck lights or another type of light that can be hidden by an architectural feature. Metallic, fluorescent and day-glow paints are not appropriate.

Auto-oriented Canopy/Awning Signs

The allocation of signage for auto-oriented canopies and awnings shall be measured as wall signs and shall only be used on the canopy/awning. See the section for Canopies and Awnings for information on the design of canopies and awnings.



IV. SIGNAGE

Parking Lot Signs

A pole-mounted projecting sign is allowed for surface parking lots with no associated building. One sign per street frontage is allowed. The maximum size shall be 36 square feet per sign. The side of the sign shall be attached to the pole and the pole will be considered the “building façade.” All projecting sign standards shall apply; parking lot signs shall follow the standards of a 1-story building.

KEEP IN MIND

- There is no limit to the number of Building Signs per property, with the exception of neon signs.
- Sign entitlements are limited only by the total amount of square footage allowed on the property, the maximum sizes of signs and the required placement of signs, with the exception of neon signs.
 - For example, if a building is allowed 100 sq. ft. of Building Signs, that can be use in one 100 sq. ft. sign or in five 20 sq. ft. signs. The only limit is the maximum dimensions of the sign type.
- Non-street facing facades are allowed signs.
- Contact the MHZC with questions.

IV. SIGNAGE

C. Design Guidelines: Building Sign-Wall Sign


Description

A wall sign is a building sign that is attached flat to, or mounted away from but parallel to, the building façade.

A wall sign may be painted on the building façade, in some instances, as a modification.

General Provisions

- A wall sign shall be located lower than the window sills of the top floor for multi-story buildings.
- No portion of a wall sign may extend above the roof line or above a parapet wall of a building with a flat roof.
- No portion of a wall sign may extend above the lower eave line of a building with a pitched roof.
- A wall sign cannot cover windows or architectural details.
- An exposed raceway shall be finished to match the background wall or be integrated into the overall design of the sign.
- A wall sign can be externally or internally illuminated in accordance with the section on Illumination.



Design Standards

A Overall area allocation (max)	(see allocation of sign area)
B Projection (max)	2 inch OR 13 inches for internally lighted or neon signage
C Exposed Raceway height	50% of the letter height, OR if the Raceway is used as the sign background, the Raceway may extend 3 inches beyond the largest part of the sign.

Refer to Illumination section for additional raceway standards and permitted locations.





IV. SIGNAGE

D. Design Guidelines: Building Sign-Awning Sign

Description

Awning Signs are a type of building sign. Graphics and symbols are painted, sewn or otherwise adhered to the awning material as an integrated part of the awning itself.

General Provisions

- Only awnings on first and second story windows may contain signs.
- A maximum of one sign is allowed per awning face.
- An awning sign may only be externally illuminated.
- See the Awnings section of the design guidelines for additional information on the design of awnings.
- An awning sign cannot cover architectural details.




Design Standards

A Overall area allocation (max) (see allocation of sign area)

B Sign Width (max % of awning width/depth) 75%

C Height of text and graphics on valance (max) 2 feet

D Max area of sloping plane covered by sign 50%



IV. SIGNAGE


E. Design Guidelines: Building Sign-Canopy Sign

Description

A canopy sign is a type of building sign that is attached above, below or to the face of a canopy.

General Provisions

- A canopy sign cannot extend outside the overall length or width of the canopy. However a canopy sign may extend above or below the canopy provided the sign meets all other design standards.
- Maximum of one sign per canopy face.
- Raceways are permitted for signs extending below or above the canopy.
- A canopy sign can be externally or internally illuminated in accordance with the Illumination section.
- Cabinet signs are not permitted as canopy signs.
- A canopy sign cannot cover architectural details.



See the Awning/Canopy section of the design guidelines for additional information on the design of canopies.

- This definition does not include freestanding canopies over fuel pumps.

Design Standards

A Overall area allocation (max)	(see allocation of sign area)
B Sign Width	75%
C Height of text and graphics (max)	2 feet
D Depth (max)	13 inches
E Exposed Raceway height (max)	50% of the letter height OR if the Raceway is used as the sign background, the Raceway may extend 3 inches beyond the largest part of the sign.



Refer to illumination section for additional raceway standards and permitted locations.



IV. SIGNAGE


F. Design Guidelines: Building Sign-Projecting Sign

Description

A projecting sign is a type of building sign that projects outward from the façade, typically at a ninety degree angle. Projecting signs are typically, but not always, vertically oriented and generally mounted above the first floor.

General Provisions

- A projecting sign must be located at least 25 feet from any other projecting sign. When building width prohibits adherence to this standard, flexibility shall be permitted through Modification to be reviewed by staff.
- A projecting sign may be erected on a building corner when the building corner adjoins the intersection of two streets. Allocation of sign area from both streets may be used, however, in no case shall the sign exceed the maximum dimensional standards below.
- A projecting sign shall be located below the windows sills of the third story.
- The top of a projecting sign shall not extend above the building eave or top of parapet.
- A projecting sign can be externally or internally illuminated in accordance with the Illumination design guidelines.
- Projecting signs that are 3-dimensional may be permitted through a modification.
- A projecting sign cannot cover windows or architectural details.



Design Standards

A Overall area allocation (max)	(see allocation of sign area)
B Height (max)	
1 story buildings	10 feet
2 and 3 story buildings	16 feet
4 or more story buildings	20 feet
C Average spacing from façade (min)	1 foot
D Projection Width (max)	6 feet
E Depth of Cabinet (max)	2 inch or 18 inches for internally lighted or neon signage

IV. SIGNAGE

G. Design Guidelines: Building Sign-Shingle Sign

Description

A single sign is a smaller building sign that projects outward, typically at a ninety degree angle, and hangs from a bracket or support that is located over or near a building entrance.

General Provisions

- Signs shall be located within 8 feet of an active pedestrian building entrance. This does not include service entries or entries that primarily remain locked.
- An active pedestrian entrance at the corner of a building is allowed signs on both streets.
- A shingle sign shall be located below the window sills of the second story.
- A shingle sign shall not be internally illuminated.
- A shingle sign cannot cover windows or architectural details.



Design Standards

A Area (max)	9 square feet
B Height (max)	3 feet
C Spacing from façade (min)	6 inches
D Width (max)	3 feet
E Depth (max)	6 inches





IV. SIGNAGE

H. Design Guidelines: Building Sign-Monument Sign

Description

A monument sign is a ground sign that is attached along its entire length to a continuous pedestal.

General Provisions

- Monument signs shall only be allowed when the existing building face is set back from the public right-of-way by at least 20’.
- Each property, which allows a monument sign, is permitted one per street frontage. One additional monument sign is allowed for properties with 300 or more feet of street frontage on one street. Where more than one sign is permitted, signs along the same street frontage shall be spaced a minimum of 200 feet apart.
- A monument sign must be set back at least 5 feet from the front property line.
- A sign erected on the top of a retaining wall is required to meet the standards for a monument sign. The height of the wall shall be included in the overall height calculation. In this case, the 5 foot minimum setback is not required.
- A sign affixed to the face of a retaining wall or seat wall that is an integral part of a plaza or streetscape design may utilize the sign area allocated to wall signs. In this case, the 5 foot minimum setback is not required.
- A monument sign can be externally or internally illuminated in accordance with the Illumination section of the design guidelines.

Design Standards

A Sign area (max per sign)	(see allocation of sign area)
B Height (max)	5 feet
C Depth (max)	18 inches





IV. SIGNAGE

I. Design Guidelines: Building Sign-Skyline Sign

Description

A building sign is attached flat to or mounted away from the building façade. Sign may be parallel to the building façade or vertical. Located on the upper band of a building.

General Provisions

- A skyline sign is only allowed on buildings greater than 75 feet in height.
- A skyline sign must be located within the top third of the building.
- No portion of a skyline sign may extend above the roof line or above a parapet wall of a building with a flat roof.
- No more than one skyline sign per façade is allowed. However, additional skyline signs may be allowed as a Modification for Exceptional Design.
- Raceways are not permitted on skyline signs.
- A skyline sign can be internally (but not externally) illuminated in accordance with the Illumination section of the design guidelines.



Design Standards

A Area (max)	(see allocation of sign area)
B Height (max)	14 feet
C Width (max % of façade length)	50%





IV. SIGNAGE

J. Design Guidelines: Signage Illumination

Illumination of signs shall be in accordance with the following requirements:

External Illumination

- External light sources shall be placed close to, and directed onto the sign and shielded to minimize glare into the street, sidewalks or onto adjacent properties.
- Projecting light fixtures used for externally illuminated signs shall be simple and unobtrusive in appearance. They should not obscure the sign.

Internal Illumination

- Channel letters may be internally lit or back-lit.
- For cabinet signs, the background must be opaque. Only graphics, text and logos may be illuminated, and a halo of one inch around graphics, text, and logos may be non-opaque.
- Exposed neon may be used for lettering or as an accent.

Prohibited Light Sources

The following light sources are prohibited:

- Blinking, flashing, chasing, and sequential lighting.
- Bare bulb illumination.

Raceways and Transformers

- Visible transformers are prohibited.



External light sources



Internally lit channel letters



Back lit channel letters



Internally lit cabinet signs with darker backgrounds



IV. SIGNAGE

K. Design Guidelines: Changeable Copy/Electronic Signs

Changeable copy signs shall be in accordance with the following requirements:

Description

- Manual changeable copy sign. A sign or portion of a sign that has a readerboard for the display of text information in which each alphanumeric character, graphic or symbol is defined by objects, not consisting of an illumination device. Changeable copy is changed or re-arranged manually or mechanically without altering the face or the surface of the sign.
- Electronic changeable copy sign. A sign or portion of a sign that displays information in which each alphanumeric character, graphic, or symbol is defined by a small number of matrix elements using different combinations of light emitting diodes (LED's), fiber optics, light bulbs or other illumination devices within the sign.

Usage

- Manual and Electronic changeable copy is allowed for Tourist Oriented Businesses only when used in conjunction with a wall sign or a monument sign provided the changeable copy portion is no greater than 50% of the built sign area.
- An electronic changeable copy sign is not allowed in a Redevelopment District or on Interstate frontage.

Spacing

- The closest edge of an electronic changeable copy sign must be a minimum distance of 100 feet from any residential zoning district.
- An electronic changeable copy sign must be separated from another electronic changeable copy sign by at least 50 feet.

Duration

- Any image or message or portion of the image or message must have a static display for minimum duration of eight seconds.
- Transition time must be immediate.
- No portion of the image or message may flash, scroll, twirl, change color or in any manner imitate movement.

Brightness

- The sign must not exceed a maximum illumination of 7,500 nits during daylight hours and a maximum illumination of 750 nits between dusk to dawn as measured from the sign's face at maximum brightness.
- Electronic changeable copy signs must have an automatic dimmer control to produce a distinct illumination change from a higher illumination level to a lower level.



IV. SIGNAGE

This page intentionally left blank.

V. DEMOLITION

Demolition

General Principles

Since the purpose of historic zoning is to protect historic properties, the demolition of a building that contributes historically and architecturally to the character and significance of the district is not appropriate and should be avoided.

Demolition is considered the removal of any structure or portion of a structure that affects the visual appearance of the building from the exterior. *It includes the removal of floors or sections of the building that are enclosed by the original façade.*



V. DEMOLITION

Guidelines: Demolition

1. Demolition is inappropriate:
 - a. if a building, or major portion of a building, contributes to the architectural or historical significance or character of the district; or
 - b. if a building, or major portion of a building is of such old or unusual or uncommon design and material that it could not be reproduced without great difficulty and expense.

2. Demolition is appropriate:
 - a. if a building or a major portion of a building does not contribute to the historical or architectural character and importance of the district; or
 - b. if a building or a major portion of a building has irretrievably lost its architectural integrity and importance and its removal will result in a more historically appropriate visual effect on the district; or
 - c. if the denial of the demolition will result in an economic hardship on the applicant as determined by the MHZC in accordance with section 17.40.420, as amended, of the historic zoning ordinance.



VI. APPENDIX

Definitions

Addition: New construction that increases the footprint, height, or building envelope of an existing structure.

Alteration: A replacement or change in a building material; the addition or elimination of any architectural element of a building; a repair that reconstructs any part of an existing building; construction of, or change to, an appurtenance.

Appropriate: Suitable for, or compatible with, a property or district, based on accepted standard and techniques for historic preservation.

Appurtenances: Fences, walls, paving, streetlights, curbs, gravel, signs, satellite dishes, fountains, mailboxes, and other accessory or adjunct permanent built features related to a building or streetscape.

Awning: An awning is a secondary covering attached to the exterior wall of a building without additional supports and is located above a window or entrance. It is typically a metal frame covered in canvas. With the addition of columns or posts an awning becomes a canopy,

Canopy: A covered area which extends from the wall of a building to protect an entrance or loading dock. Also see “Awning”.

Certificate of Appropriateness: See Preservation Permit.

Character-Defining Features: Individual physical elements of any structure, site, street, or district that contribute to its overall historic or architectural character, and for which it is recognized as historically or architecturally significant.



VI. APPENDIX

Demolition: *The tearing down of a building in whole or in part.*

Elevation: *A scaled drawing that illustrates the view of a side of a building.*

Facade: *An exterior side of a building.*

Gobo Light:: *A light fixture that has a stencil or template placed inside or in front of the a light source to control the shape of emitted light.*

Historic: *A structure or site, usually constructed by 1957 or earlier, which possesses historical or architectural significance, based on the criteria for listing in the National Register of Historic Places.*

Marquee: *A permanent roof-like shelter over an entrance to a building. Marquees are usually flat roofed and sometimes have supporting posts on the side opposite the side of the marquee that attaches to the building and may include signage and lighting. Historically, marquees were used typically for hotels and theaters. Also see “Canopy”.*

New Construction: *Any freestanding structure on a lot constructed after the designation of the conservation zoning district.*

Non-Historic: *A structure or site, usually constructed after 1957, which does not possess historical or architectural significance, based on the criteria for listing in the National Register of Historic Places.*

Orientation: *The directional expression of a building’s front façade.*



A Gobo light as seen on Second Avenue’s sidewalk.



VI. APPENDIX

Period of Significance: *The time frame in which a neighborhood developed or was platted into building lots and substantially built out with structures, based on the criteria for listing in the National Register of Historic Places.*

Preservation Permit: *A legal document issued by the Metropolitan Historic Zoning Commission confirming review and approval of work to be done on property within the boundaries of an historic or conservation zoning district. A preservation permit is required before getting a building permit. Previously called Certificate of Appropriateness.*

Public Facade: *The exterior faces of buildings that front public streets.*

Public Right of Way: *A publicly owned and maintained street or walkway.*

Public Space: *Any area that is either owned, leased or for which there is held an easement by a governmental entity, or an area that is required to be open to the public.*

Reconstruction: *Construction of an accurate replica of a historic building or portion thereof, based on physical, pictorial or documentary evidence.*

Rehabilitation: *The act or process of making possible a compatible use for a property through repair, alterations, and additions while preserving those portions or features which convey its historical, cultural, or architectural values.*

Repair: *See alteration.*

Shall: *What must happen.*

Should: *What must happen unless circumstances illustrate why an alternative is more appropriate.*

METROPOLITAN HISTORIC ZONING COMMISSION

Sunnyside in Sevier Park
3000 Granny White Pike
Nashville, TN 37204

Phone: 615-862-7970
Fax: 615-862-7974

The Metropolitan Historic Zoning Commission reviews applications to create new historic overlay districts and reviews and approves preservation permits in historic and conservation districts for new construction, alterations, additions, repair and demolition. For design guidelines, permit applications, and meeting information, visit us at www.nashville.gov/mbc.

**WE ARE ON THE
WEB AT
[WWW.NASHVILLE.
GOV](http://WWW.NASHVILLE.GOV)**



The Metro Historical Commission does not discriminate on the basis of race, color, national origin, gender, gender identity, sexual orientation, age, religion, creed or disability in access to, or operation of its programs, services, activities or in its hiring or employment practices. **ADA inquiries should be forwarded to:** Yvonne Ogren, Metro Historical Commission ADA Compliance Coordinator, 3000 Granny White Pike, Nashville, TN 37204, (615) 862-7970. **Title VI inquiries should be forwarded to:** Ms. Shirley Sims-Saldana, Title VI Coordinator, Human Relations, 800 Second Avenue, South, 4th floor, Nashville, TN 37210, (615) 880-3391. **Contact Department of Human Resources for all employment related inquiries** at (615) 862-6640.