



HALF - SECTION

General Notes
 1. Placement of sidewalks shall be in accordance with the Subdivision Regulations of the Metropolitan Planning Commission, latest revision.

2. Construction shall conform to the Metropolitan Department of Public Works Technical Specifications, latest revision.

PAVEMENT SCHEDULE

- ① 1-1/2" ASPHALTIC CONCRETE SURFACE (411D)
- ② TACK COAT (SS-1)
- ③ 2" BITUMINOUS BINDER (B-M2)
- ④ TACK COAT (SS-1)
- ⑤ 4" BITUMINOUS BASE (307A)
- ⑥ PRIME COAT (RS-2)
- ⑦ 10" STONE (GRADING D PUG MILL MIX)

NOT TO SCALE

PAVEMENT COURSES

METROPOLITAN GOVERNMENT OF NASHVILLE AND DAVIDSON COUNTY DEPARTMENT OF PUBLIC WORKS		NON-RESIDENTIAL DIVIDED STREET (88' MINIMUM R.O.W.)		DWG. NO. ST-262	
ASST. DIR. ENG.: <i>Mark May</i>		DATE: 5/3/01		REVISED: 04/09/01	
DIRECTOR: <i>R. [Signature]</i>		DATE: 5/8/01			